

FLEX TRACK® 4230

Issue Date: 5/15/2023 Version 1.0

DESCRIPTION

Jessup Series Flex Track® 4230 is a yellow coarse-textured anti-slip PVC safety tape engineered with an aggressive adhesive to adhere to a wide variety of surfaces. A perfect solution to outline traffic patterns within a warehouse. Able to withstand modest fork truck traffic (avoid tire rotation).

APPLICATION & FEATURES

- Indoor and outdoor non-skid applications
- UL410 certified
- ADA & OSHA compliant
- Durable
- Good chemical resistance

PROPERTIES

PHYSICAL PROPERTIES	TEST METHODS	AVERAGE RESULTS
Thickness	PSTC - 133 - Substrate - Pressure Sensitive adhesive - Release Liner	0.026 inch (0.660 mm) 0.002 inch (0.051 mm) 0.0065 inch (0.165 mm)
Peel Adhesion to: - Stainless Steel	PSTC – 101 15-minute dwell 24-hour dwell	95 oz/in (105 N/100 mm) 120 oz/in (131 N/100 mm)
Shear Adhesion to: - Stainless Steel	PSTC – 107 1/2" x 1/2" x 1000g	≤ 2 hours
Tack	PSTC - 6 Rolling Ball Tack	10+ inches
Temperature Range - Application Temperature - Operating Temperature		50°F -10 - 200°F

PHYSICAL PROPERTIES	TEST METHODS	AVERAGE RESULTS
Coefficient of Friction (Kinetic)	ASTM D1894 Dry Rubber Wet Rubber Dry Leather Wet Leather	0.9 1.0 0.3 1.0
CERTIFICATIONS	UL410, ASTM D2047	
CHEMICAL PROPERTIES	REAGENT	RECOMMENDATION
<u>Solvent Resistance</u> (Product laminated to stainless steel panel and allowed to condition for 24 hours at room temperature before testing. Sample was covered with reagent to the point that edges of product are also exposed to the reagent. The product is exposed to reagent for one hour at room temperature, then reagent is removed, and product is immediately tested for scrape resistances, delaminating, and other visual effects.)	Water 10% Salt Water Bleach Trichloroethylene 25% Sulfuric Acid 1% Sodium Hydroxide Unleaded Gasoline All Purpose Cleaner 50% Antifreeze in water MEK Mineral Spirits 99% IPA	Recommended Recommended Recommended Not Recommended Intermittent Contact Only Recommended Recommended Recommended Recommended Not Recommended Recommended Recommended

Note: While the data contained herein is believed to be reliable averages of the product's properties, the data should not be used for specification purposes. Test Data and results contained in this document are for general guidance only and should not be used by customers to establish designs and specifications. Customers who desire specific performance data should contact Jessup Manufacturing Company for further recommendations.

WARRANTY

Jessup Manufacturing Company products are warranted to be free of defects in material and manufacture at the time of shipment and to meet the specifications stated in the Technical Specifications Sheets. Jessup Manufacturing Company will replace or refund the price of any Jessup Manufacturing Company materials found not to meet our product specifications. In no case shall Jessup Manufacturing Company be liable for any direct, indirect, or consequential damages; including labor or non- Jessup Manufacturing Company materials charges.

**The determination of the suitability of this product for any specific use is solely the responsibility of the user. No representations, guarantees or warranties of any kind are made to the accuracy or suitability for specific application