

Introducing

# JESSUP ARMORLam<sup>®</sup> 15

*Virtually Invisible Overlamine*

Jessup ARMORLam<sup>®</sup> 15 is the perfect choice for any printer looking for an anti-slip overlamine. This 15 mil thick, ultra-clear, PVC free polyester product offers essential safety, durability and UV protection for up to 12 months. Not only is it great for indoor/outdoor graphics in dry applications, but its superior slip resistance makes it ideal for use on wet surfaces as well. ARMORLam<sup>®</sup> 15 meets OSHA and ADA standards and is mop friendly, making it easier to clean than alternative solutions. Trust Jessup ARMORLam<sup>®</sup> 15 on all your complex graphics projects!



Holds up under heavy foot traffic



Protect your graphics with our high UV resistant solution

Foot friendly surface rated **R11** for high traction slip resistance



Super clear polyester film



Non PVC for a earth friendly solution



Holds up under wet conditions



Easy to clean with mops and floor scrubbers

Extend the life of a graphic by months or years



**J** JESSUP<sup>®</sup>  
Adhesive Coated Films

[jessupmfg.com](http://jessupmfg.com)

# JESSUP ARMORLam® 15

Virtually Invisible Overlaminates

## Application Ideas:

- Airports
- Car dealerships
- Floor decals
- Hospitals
- Museums
- Point-of-purchase displays
- Retail and advertising
- Restaurants
- Swimming pools
- Theme parks
- Water parks
- Warehouses



Scan to see video



## Use ARMORLam® with these Jessup recommended graphics media:

- WallPro™ 3
- WallPro™ 4
- TexWalk Smooth®
- Smooth-N-Groove®
- TenaciousTac™ 1, 2, 2CR, 4

## UV print compatible

### Duration:

12+ months depending upon use, environment, and application

### Sizes:

- OL-CLRGLS-54"x150'
- OL-CLRGLS-27"x10'

### Certifications:

- R11 DIN EN 16165:2023-02
- B101.3

PHYSICAL PROPERTIES	TEST METHODS	AVERAGE RESULTS
Thickness	PSTC - 133 - Substrate - Pressure Sensitive adhesive - Release Liner	0.014 inch (0.330 mm) 0.001 inch (0.031 mm) 0.0065 inch (0.165 mm)
Peel Adhesion to:	PSTC – 101	
- Stainless Steel	15 minute dwell 24 hour dwell	60 oz/in (66 N/100 mm) 75 oz/in (83 N/100 mm)
- Powder coated surfaces *	15 minute dwell 24 hour dwell	55 oz/in (27 N/100 mm) 70 oz/in (27 N/100mm)
- Polyethylene	15 minute dwell 24 hour dwell	25 oz/in (61 N/100 mm) 25 oz/in (77 N/100 mm)
Shear Adhesion to:	PSTC – 107	
- Stainless Steel	1/2" x 1/2" x 1000g	5 hours
Tack	PSTC - 6 Rolling Ball Tack	< 5 inches

\* Color and lot variances of coated surfaces including paints, powder coatings, lacquers, stains, and other treatments may vary the performance of the tape and should be evaluated for the compatibility of the tape to the specific surface.



Order now: 1-888-711-7735.

Jessup Manufacturing Company  
©2024 Jessup • MKT-JMC-ARMORLam15



jessupmfg.com